

PRODUCT DATA SHEET

DECCOBOND 300

Melamine & Vinyl Glue

PRODUCT NAME: DECCOBOND 300**PRODUCT DESCRIPTION:**

Deccobond 300 is a polymer based emulsion adhesive formulated for modern gluing operation where fast setting time with good bond strength.

APPLICATION:

Deccobond 300 is suitable for lamination of PVC films or vinyl laminates to blockboard, chipboard and plywood.

PHYSICAL PROPERTIES:

Appearance:	White emulsion
Solid:	55.0 – 56.0%
pH:	4.0 – 5.0
Odor:	Mild, None when dry
Viscosity:	4,500 – 5,500 cps (Brookfield RVF Spindle 4, 20rpm at 26° C)
Specific Gravity:	1.058
Flammability:	Non flammable
VOC:	9.0 g/L
LEED:	Compliant

LEED Compliant
Water-based Tech

PREPARATION:

Deccobond 300 is supplied ready to use and do not require mixing.

USAGE:

Surfaces to be glued must be clean and free from dust, grease or oil. If present on the surface, it must be cleaned with solvents or thinners.

CLEANING:

Machines, brushes, rollers, glue guns & spreaders can be easily cleaned with water & sponge. Warm water cleans better. Keep application equipment in water after use for easier cleaning.

STORAGE:

Deccobond 300 is stable. Stores well for at least 9 to 12 months at room temperature.

KEEP FROM FREEZING:

For Industrial & Professional Use

PACKING:

Pail, Drum, Tote

