

PRODUCT DATA SHEET

DECCOBOND 920

Vinyl Glue

PRODUCT NAME: DECCOBOND 920 – Vinyl Glue

PRODUCT DESCRIPTION:

Deccobond 920 is a polymer based emulsion adhesive for modern gluing operation with fast setting time and good bond strength.

APPLICATION:

Deccobond 920 is suitable for machine application. Packaging application, used for difficult to bond surfaces and very low energy surfaces & films. Deccobond 920 is suitable for machine application.

PHYSICAL PROPERTIES:

Appearance:	White emulsion
Solid:	54.5 – 55.5%
pH:	4.0 – 5.0
Odor:	Mild, None when dry
Viscosity:	1,800 – 2,400 cps (Brookfield RVF Spindle 4, 20rpm at 26° C)
Specific Gravity:	1.08
Flammability:	Non flammable
VOC:	5.0 g/L
LEED:	Compliant

LEED Compliant
Water-based Tech



PREPARATION:

Deccobond 920 is supplied ready to use and do not require mixing.

CLEANING:

Machines, brushes, rollers, glue guns & spreaders can be easily cleaned with water & sponge. Warm water cleans better. Keep application equipment in water after use for easier cleaning

STORAGE:

Deccobond 920 is stable. Store well for at least 12 months at room temperature at 20 degree C. Do not store next to heaters or very high temperature of 65 degree C or more. Deccobond 107 is packed in plastic or polyethylene containers.

KEEP FROM FREEZING:

For Industrial & Professional Use

PACKING:

Pail, Drum, Tote

