



Since 1990

DECCOBOND 170

Litho Lamination & Mounting Glue

DESCRIPTION:

DECCOBOND 170 is a polymer based emulsion adhesive formulated for gluing operation where long open time, non-curling and non-warping are required.

APPLICATION: **DECCOBOND 170** is suitable for laminating, overlaying, roll coat or spraying on cardboard, blockboard and corrugated boards. It is ideal for lay-flat mounting printed paper materials on paper boards for machine or manual application.

PREPARATION & USAGE:

DECCOBOND 170 is supplied ready to use and do not require mixing. Surfaces to be glued must be clean and free from dust, grease or oil. If present on the surface, it must be cleaned with solvents or thinners.

CLEAN UP:

Tools, glue line, injection heads, glue guns and spreaders can be easily cleaned with water and sponge. Warm water cleans better. Keep application equipment in water after use for easier cleaning.

STORAGE:

DECCOBOND 170 is stable. Stores well for at least 9 to 12 months at room temperature of 20° C. Do not store next to heaters or very high temperatures of 65° C or more. **DECCOBOND 170** is packed in plastic or polyethylene containers. Do not store in unlined metal containers as there will be reactions between the adhesive and the unlined container resulting in dark stains and contaminants. **KEEP FROM FREEZING.**

VOC Compliant:

Compliant to 21 CFR 175.105 for adhesive intended for incidental food contact.



PHYSICAL PROPERTIES

Type	White emulsion	Viscosity	1,200 – 2,200 cps
Appearance	White	Odor	Mild to None
Solids	53.5–55.5 %	Flammability	Non-flammable
Specific Gravity	1.10	VOC	1.1 g/L

PACKING INFORMATION

Size	Pail/Pallet
5 gallon pail	36
55 gallon drum	-
275 gallon tote	-



TENCO WESTECH POLYMERS INC.
160-6333 Graybar Road, Richmond, B.C.
Canada V6W 0C4 t 604-276-8538